The School District of Newberry County Request for Proposals Metal Locker Replacement/Renovation Projects



The School District of Newberry County is accepting proposals for student metal locker replacement at Newberry High School (200 wing) and student metal locker renovations at Newberry High School (100 and 300 wings) and Mid Carolina Middle School (7th & 8th Grade wings).

All proposals are to be submitted (hand delivered or mailed) to Mr. Kenneth Rawls at The School District of Newberry County district office located at 1539 Martin Street, Newberry, SC 29108. Any questions can also be directed to Mr. Rawls by email at <u>krawls@newberry.k12.sc.us</u> or phone at 803.924.3848.

All sealed proposals must be received by April 15, 2011 at 2:00pm. All proposals must include a minimum of three (3) references with contact information.

All proposals will be evaluated by a district committee. The following criteria/weighting will be used to evaluate each proposal:

Quality of product/service-	20%
Ability to complete project in a timely manner-	20%
Industry/School related experience-	20%
Pricing-	30%
References-	<u>10%</u>
	100%

Please note that price is a weighted factor, however it will not be the sole determination in awarding this project.

A mandatory site visit to verify measurements and specifications is scheduled for April 11, 2011 at Newberry High School 3113 Main Street, Newberry, SC 29108 at 10:00am followed with a visit to Mid Carolina Middle School 6834 US Highway 76, Prosperity, SC 29127.

PROJECT SPECIFICATIONS

*DOUBLE TIER STUDENT CORRIDOR LOCKERS

New Lockers will be a knocked down assembly double tier with nuts and bolts.

Doors will be 16ga. mild cold rolled steel with a 24ga. mild cold rolled body.

Two full loop 2" 5- knuckle hinges per door nested in door slot welded to frame and double-riveted to door. Handles will be stainless steel recessed with plastic protected lifting trigger able to accept padlock or built-in locks.

Doors will latch at multi-points (2).

Doors may or may not have ventilation louvers.

Locker units will be 12"W X 12"D X 36"H double tier.

All metal lockers will have sloped tops.

All lockers will have number plates: 2 ¹/₄ w X 1" h with black numbers 3/8" high. Plates shall be attached with 2 aluminum rivets. Number sequence to be provided by owner.

INSTALLATION

Install metal lockers and accessories level, plumb, rigid, and flush according to manufacturer's written instructions.

Connect all lockers together with standard fasteners, with no exposed fasteners on face frame. Anchor lockers to floor and walls at intervals recommended by manufacturer.

ADJUSTING AND CLEANING

Adjust all units to operate easily and freely without binding.

Clean interior and exposed exterior surfaces.

Touch up marred finishes, use only materials and procedures recommended or furnished by locker manufacturer.

***DOUBLE TIER LOCKER RENOVATIONS**

Restore lockers to a like new condition.

Tightening and replacing loose/missing nuts and bolts on all lockers.

Aligning locker doors to operate easily and freely without binding; replacing all doors that are either missing or irreparable.

Securing loose shelves and other parts.

Replacing broken latches, handles, and number plates. Number sequence to be provided by owner.

Provide and install new slope tops on all renovated lockers.

Properly prepare the old surface and refinish all lockers with a new surface coating equal to original appearance.

The School District of Newberry County reserves the right to refuse any and all proposals and waive informalities and minor irregularities in proposals received.